

Information to be completed by USER for equipment that may be used in potentially explosive atmospheres

		√	PLEASE TICK
1	UN-ZONED AREA		Dangerous Substances and Explosive Atmospheres Regulations 2002 (DSEAR/ATEX) NOT APPLICABLE
2	Potentially explosive atmosphere of air and		GAS/VAPOUR
			DUST
3	Zone classification the machine will be installed in (group II)		0 (Gas/Vapour)
			1 (Gas/Vapour)
			2 (Gas/Vapour)
			20 (Dust)
			21 (Dust)
			22 (Dust)
4	Allowable surface temperature (group II)		T6 (85 C)
			T5 (100 C)
			T4 (135 C)
			T3 (200 C)
			T2 (300 C)
			T1 (450 C)
5	Dust characteristic		Conductive
			Non-Conductive
	Type of dust/gas:		
	Kst value:		
	St class:		
	Minimum Ignition Temp - cloud:		
	Minimum Ignition Temp - layer:		
	Minimum Cloud Ignition Energy:		
	NAME :		
	POSITION :		
	COMPANY :		
	SIGNATURE:		
	DATE :		

NOTES TO USER

According to the DSEAR/ATEX regulations end users **MUST** establish if a potentially explosive atmosphere is likely to occur and if so give an appropriate Zone classification.

Explosive atmospheres may be caused by gases/vapours or dust

Zones are classified according to BS EN 1127-1:1997

Explosive atmospheres may be ignited by surface temperature. Please enter the allowable surface temperature according to the gases/vapours or dust that may be present.

Dusts may be CONDUCTIVE or NON-CONDUCTIVE, please specify.

Stock Redler Ltd. require the above information to ensure the correct equipment is supplied.

**Stock Redler regrets it is unable to offer advice regarding Zone classification.
Guidance on Zone classification may be obtained from
BS EN 1127-1:1997 or the local Factory Inspector**